

# SPECIFICALLY DESIGNED TO MEET YOUR REQUIREMENTS - FOR ANY AND ALL WORKING ENVIRONMENTS

Anchor drums are mounted on heat-treated alloy steel shaft, and pivot on high quality tapered, anti-friction roller bearings. Drum surface is smooth or machine grooved for precision line spacing. Center point mounted for optimum weight indicator accuracy without correction factor, regardless of radial line pull off angle. Aluminum bronze wire line clamp inserts provide a secure cable grip without line damage. After assembly each anchor is proof tested to 150% of rated capacity, using the largest cable size for which it was designed. (All proof tests are held for a full 5 minutes) After testing, entire anchor is sandblasted to white metal, coated with zinc rich primer for corrosion protection and painted with heavy duty industrial enamel.

AVAILABLE WORLDWIDE THROUGH WEIGHT INDICATOR  
MANUFACTURERS



New "SG" Series SUPER GRIP  
specifically designed for use with Plastic Filled  
Valley Wire Rope (PFV) - holds wireline  
securely with :ZERO LOAD " at the line clamp.

HA120T - "SG"  
HA130T- "SG"  
HA150T- "SG"

## STANDARD HERCULES ANCHORS FOR USE WITH STANDARD WIRE LINE

MODEL	RATED DEADLINE PULL	LOAD SENSOR		WIRELINE SIZE	WIRE TYPE		DRUM DIAMETER	APPROX. WEIGHT	MOUNTING	
	[lbs]	TYPE	SIZE		PFV*	STANDARD			ORIENTATION	QTY - GRADE 8 BOLTS
HA160-T-SG	160,000	COMPRESSION	50 in <sup>2</sup>	1 5/8" - 2"	X	X	38.50	3495	BASE	4 - 2 1/2"
HA160-T-RD	160,000	COMPRESSION	50 in <sup>2</sup>	1 5/8" - 2"		X	38.50	5211	BASE	4 - 2 1/2"
HA150-T-SG	150,000	COMPRESSION	50 in <sup>2</sup>	1 5/8" - 2"	X	X	36.00	3212	BASE	4 - 2 1/4"
HA131-T	100,000	TENSION	36.7 in <sup>2</sup>	1 1/4" - 1 5/8"		X	27.88	1467	BASE	4 - 2"
HA130-T-SG	130,000	COMPRESSION	50 in <sup>2</sup>	1 1/2" - 1 3/4"	X	X	31.00	2173	BASE	4 - 2 1/4"
HA130-T	130,000	COMPRESSION	50 in <sup>2</sup>	1 1/2" - 1 3/4"		X	31.00		BASE	4 - 2 1/4"
HA129-T	60,000	TENSION	36.7 in <sup>2</sup>	1" - 1 1/4"		X	24.00	836	BASE	4 - 1 1/2"
HA120-T-RD	100,000	COMPRESSION	50 in <sup>2</sup>	1 1/4" - 1 5/8"		X	28.00	2273	BASE	4 - 2"
HA120-TML-RD	100,000	COMPRESSION	50 in <sup>2</sup>	1 1/4" - 1 5/8"		X	28.00	2822	SIDE	9 - 1 3/4"
HA120-T-SG	100,000	COMPRESSION	50 in <sup>2</sup>	1 1/4" - 1 5/8"	X	X	28.00	1804	BASE	4 - 2"
HA120-TML-SG	100,000	COMPRESSION	50 in <sup>2</sup>	1 1/4" - 1 5/8"	X	X	28.00	2121	SIDE	9 - 1 3/4"
HA119-TML	60,000	COMPRESSION	36.7 in <sup>2</sup>	1" - 1 1/4"		X	24.00	763	SIDE	4 - 1 1/2"
HA118-TML	45,000	COMPRESSION	16.1 in <sup>2</sup>	7/8" - 1 1/4"		X	16.00	365	SIDE	4 - 1"
HA118-T	45,000	COMPRESSION	16.1 in <sup>2</sup>	7/8" - 1 1/4"		X	16.00	592	BASE	4 - 1 1/2"
HA117-TML	30,000	COMPRESSION	16.1 in <sup>2</sup>	5/8" - 1"		X	10.00	168	SIDE	4 - 3/4"

\*PLASTIC VALLEY FILLED

